



SHANDONG KUNDU CHEMICAL CO.,LTD.

ADD: No.17 Huanghe Industry Park, Jinan city, Shandong, China

Tel: +86 131 5314 4592 Fax: +86 531 82924317

Email: info@kdchemicals.com

www.kdchemicals.com

Redispersible polymer powder KD 6012T

Product Data

KD 6012T is a spray dried Vinyl acetate/ethylene copolymer, with protection colloid of vinyl alcohol.

It redispersed in water and reacts with hydrate product of cerement/gypsum and stuffing, form composite membrane with good mechanics intensity.

Specifications

Appearance: White free flowing powder

Particle size D50 um: App.70~100

Bulk density: 400~600 gram/litre

Typical properties

Solids content (%)	98 min
Ash content (%)	8~12
PH Value	5.0~8.0
Viscosity of 50% water Solution at 25 °C (PaS)	0.5~2.0
MFFT (°C)	4

Applications

KD 6012T improves adhesion, flexural strength, abrasion resistance and workability of modified compounds such as tile adhesives, repair mortars, thermal insulation systems.

It is therefore compatible with mortar additives used to achieve special processing characteristics

KD6012T contains a fine, mineral filler as anti-block agents. It is free of solvents, plasticizers and film-forming aids.

Main uses:

- Tile adhesive
- Tile Grout
- Repair mortar

Storage

Redispersible polymer powder should be stored in cool and dry environment. It is recommended to use within 6 months, preferably be used as soon as possible in summer. Storage in high temperature and humidity conditions will increase the risk of caking. Opened containers should be used as soon as possible, if not, should be resealed to prevent ingress of moisture from the air.

Redispersible polymer powder supplied in paper bags should not be stacked. Prolonged heavy pressure may cause caking. Storage under pressure should also be avoided.

Packaging

- 25 kg paper bags inner with PE bags
- Jumbo Bags (500 kg)
- According to customer's requirement